

PERTAMINA PROTECTO C

PERTAMINA PROTECTO C is high quality industrial detergent & cleaning agent formulated from naphthenic base oil and selected additives for the effective cleaning & removing sludge and deposit.

TYPICAL CHARACTERISTICS		
Characteristic	Test Method	PERTAMINA PROTECTO C
ISO VG	-	10
Appearance	-	Clear
Density at 15 °C, Kg/L	ASTM D - 4052	0.8740
Kinematic Viscosity at 40 °C, cSt	ASTM D - 7279	10.93
	at 100 °C, cSt	ASTM D - 7279
Viscosity Index	ASTM D - 2270	80
TBN, mg KOH/g	ASTM D - 2896	7.37
Flash Point, °C	ASTM D - 92	160

SUPERIORITIES

- Good detergency & dispersancy characteristic .
- Low viscosity to provide excellent flow ability.
- Easily to dissolve sludge & deposit to maintain system cleanliness.
- Good protection against rust & corrosion.

APPLICATION

PERTAMINA PROTECTO C is recommended as cleaner and injected to circulating system partially to remove sludge & deposit. It can't be used in straight for circulating oil or heat transfer fluid.

HEALTH AND SAFETY

Please contact our Industrial Lubricants Marketing Head Office to get Material Safety Data Sheet as information for Health and Safety Protection at work.

Phone: 62-21 3190 7195. Fax : 62-21 3190 7992.

Website: www.pertamina.com or

Email: pelumas@pertamina.com