

FASTRON DIESEL SAE 15W-40

FASTRON DIESEL SAE 15W-40 is a synthetic premium quality diesel engine oil.

TYPICAL CHARACTERISTICS		
Characteristic	Test Method	FASTRON DIESEL
SAE Viscosity Grade	-	15W-40
Density at 15 °C, kg/l	ASTM D - 4052	0.8698
Kinematic Viscosity, at 40 °C, cSt	ASTM D - 7279	102.2
at 100 °C, cSt	ASTM D - 7279	14.48
Viscosity Index	ASTM D - 2270	146
ASTM Colour	ASTM D - 1500	L 4.0
Flash Point, °C	ASTM D - 92	232
Pour Point, °C	ASTM D - 5950	-24
Total Base Number, mgKOH/g	ASTM D - 2896	11

PERFORMANCE LEVEL

FASTRON DIESEL SAE 15W-40 meets below performance levels :

- API CI-4/SL
- ACEA E7, A3/B4
- MB-Sheet 228.3
- MAN 3275/271
- Volvo VDS-3
- MACK EO-M Plus
- Cummins CES 20078
- CAT ECF-2

SUPERIORITIES

- Stable viscosity that gives optimum acceleration & engine protection during start up and high temperature operation.
- High durability against oxidation & high temperature that prolongs oil lifetime.
- Low oil volatility that gives low oil consumption and assures optimum lubrication.
- Prevents corrosion, piston deposit formation and maintain engine cleanliness that prolongs engine life time.
- Very good soot control ability and acid neutralization, that are required where Exhaust Gas Recirculation (EGR) is used.

APPLICATION

FASTRON DIESEL 15W-40 is recommended for latest high speed diesel vehicle with or without EGR technology. Also suitable for engine with direct injection.

HEALTH AND SAFETY

Please contact our Marketing Head Office to get Material Safety Data Sheet as information for Health and Safety Protection at work.

Phone: 62-21 3190 7190/5. Fax : 62-21 3148884/601

Website: www.pertaminalubricants.com or email: hsse.ptpl@pertamina.com