

PERTAMINA FASTRON PLATINUM RACING

SAE 10W-60



Characteristic	Test Method	FASTRON PLATINUM RACING
SAE Viscosity Grade	-	10W-60t
Appearance	-	Clear
Density at 15 oC, kg/l	ASTM D - 4052	0.8628
Kinematic Viscosity, α 40 μ C, c St	ASTM D - 7279	157.0
at 100 μ C, c St	ASTM D - 7279	22.94
Viscosity Index	ASTM D - 2270	175
ASTM Colour	ASTM D - 1500	L 6.5
Flash Point, oC	ASTM D - 92	232
Pour Point, μ C	ASTM D - 97	-30
Total Base Number, mgKOH/g	ASTM D - 2896	11

FASTRON PLATINUM RACING SAE 10W-60 is a premium quality engine oil which is specially formulated in association with Lamborghini Squadra Corse. Designed for racing engine, it's using fully synthetic Polyalphaolefin (PAO) base oil and high performance additives to give highest performance in its class.

PERFORMANCE LEVELS

FASTRON PLATINUM RACING SAE 10W-60

meets below performance level :

- API SN
- ACEA A3/B4
- Lamborghini Squadra Corse (approved)

SUPERIORITIES

- Delivers maximum acceleration and power output.
- Excellent shear stability and high performance additives provide engine cleanliness and maximum protection from excessive wear, even in the most demanding racing application.
- Low evaporation level that gives low oil consumption and optimum lubrication.

APPLICATION

FASTRON PLATINUM RACING SAE 10W-60 is designed for racing application and also suitable for engine which requires SAE 10W-60 oil with above performance level.

HEALTH AND SAFETY

Please contact our Lubricants Marketing Head Office,

Phone: 62-21 3190 7190-95.

Fax : 62-21 3148884/601

Website: www.pertaminalubricants.com or

Email: hsse.ptpl@pertamina.com

to get Material Safety Data Sheet as information for Health and Safety Protection at work.