

PERTAMINA FASTRON GOLD

SAE 0W-20



Characteristic	Test Method	FASTRON GOLD
SAE Viscosity Grade	-	0W-20
Appearance	-	Clear
Density at 15 oC, kg/l	ASTM D - 4052	0.8444
Kinematic Viscosity, α 40 μ C, c St	ASTM D - 7279	31.65
at 100 μ C, c St	ASTM D - 7279	8.113
Viscosity Index	ASTM D - 2270	247
ASTM Colour	ASTM D - 1500	L 3.5
Flash Point, oC	ASTM D - 92	229
Pour Point, μ C	ASTM D - 97	-39
Total Base Number, mgKOH/g	ASTM D - 2896	8

FASTRON GOLD SAE 0W-20 is a synthetic premium quality engine oil.

FASTRON GOLD SAE 0W-20 has the "Perfect Balance Formulation" to exceed the stringent Japanese OEM specifications which require an outstanding engine protection and enhanced fuel economy.

PERFORMANCE LEVELS

FASTRON GOLD SAE 0W-20 meets performance level of API SN and ILSAC GF-5 (approved).

SUPERIORITIES

- Offers optimum acceleration and excellent oxidation stability that gives durable performance in all driving condition; high speed, stop and go, or heavy traffic.
- Excellent shear stability and high performance additives provide engine cleanliness and maximum protection from excessive wear.
- Low evaporation level that gives low oil consumption and optimum lubrication.

- Compatible with modern exhaust emission system technology.
- Support fuel economy improvement.

APPLICATION

FASTRON GOLD SAE 0W-20 is highly recommended for the latest car generation from the leading car manufacturers, that operate under extreme condition and require an advance fuel economy oil.

HEALTH AND SAFETY

Please contact our Lubricants Marketing Head Office,

Phone: 62-21 3190 7190-95.

Fax : 62-21 3148884/601

Website: www.pertaminalubricants.com or

Email: hsse.ptpl@pertamina.com

to get Material Safety Data Sheet as information for Health and Safety Protection at work.