

PASSENGER CAR MOTOR OILS

Product Description

A synthetic premium quality engine oil.

Applications

FASTRON GOLD SAE 5W-30 is highly recommended for the latest car generation from the leading car manufacturers, that operate under extreme condition especially gasoline engine with exhaust aftertreatment devices.

Typical Characteristics

Characteristics	Test Method	FASTRON GOLD
SAE Viscosity Grade	-	5W-30
Density at 15 °C, kg/L	ASTM D4052	0.8466
Kinematic Viscosity at 40 °C, cSt	ASTM D7279	63.51
at 100 °C, cSt	ASTM D7279	11.07
Viscosity Index	ASTM D2270	168
Flash Point, °C	ASTM D92	240
Pour Point, °C	ASTM D97	-36
Total Base Number, mg KOH/g	ASTM D2896	8

Specification / Approvals

- API SN/CF
- MB-Approval 229.51

Superiorities

- Offers optimum acceleration and excellent oxidation stability that gives durable performance in all driving conditions, high speed, stop and go, or heavy traffic.
- Excellent shear stability and high performance additives provide engine cleanliness and maximal protection from excessive wear.
- Low evaporation level that gives low oil consumption and optimum lubrication.
- Compatible with modern exhaust emission system technology.
- Support fuel economy improvement.

Health and Safety

Please contact our Industrial Marketing Head Office to get Material Safety Data Sheet as information for Health and Safety Protection
Phone: 62-21 3190 7190/5
Email: hse.ptl@pertamina.com
www.pertamilubricants.com

Disclaimer:

Information presented in this Product Data Sheet is as accurate as possible prior to printing. Such information is based upon standard industry tests under controlled laboratory conditions and presented as a guide only. To assess product suitability for its intended application, it is recommended that users refer to the latest version of the Product Data Sheet because the information contained herein is subject to change, without notice, due to the upgrades in product formulation, manufacturers' equipment specifications, user applications and storage.