

PERTAMINA FASTRON GOLD SAE 0W-20



Synthetic Premium Quality
Engine Oil



Product Description

Pertamina Fastron Gold SAE 0W-20 is a Synthetic Premium Quality Engine Oil containing “The Perfect Balance Formulation” that exceeds the stringent Japanese OEM specifications that require outstanding engine protection together with enhanced fuel economy.

Application

Pertamina Fastron Gold SAE 0W-20 is highly recommended for the latest generation of vehicles from the leading manufacturers, that operate under extreme conditions and require an advanced oil that also delivers improved fuel economy.

Performance Features

- ❖ Excellent shear stability and high-performance additives provide superior engine cleanliness resulting in reduced friction for maximum protection from excessive wear.
- ❖ Optimises acceleration and outstanding oxidation stability to deliver higher engine performance in all driving conditions, such as high speeds to continuous stop/start in heavy traffic.
- ❖ Compatible with modern exhaust emissions technologies.
- ❖ Extremely low evaporation resulting in minimal oil consumption for maximum lubrication performance.
- ❖ Provides improved fuel economy

Typical Characteristics

Characteristic	Test Method	Fastron Gold 0W-20
SAE Viscosity Grade	-	0W-20
Appearance	-	Clear
Density at 15°C, Kg/l	ASTM D – 4052	0.8444
Kinematic Viscosity, at 40°C, cSt	ASTM D – 7279	31.65
At 100°C, cSt	ASTM D – 7279	8.113
Viscosity Index	ASTM D – 2270	247
ASTM Colour	ASTM D – 1500	L 3.5
Flash Point, °C	ASTM D – 92	229
Pour Point, °C	ASTM D – 97	-39
Total Base Number, mgKOH/g	ASTM D - 2896	8

PERTAMINA FASTRON GOLD SAE 0W-20



Synthetic Premium
Quality Engine Oil



Performance Standard

Fastron Gold SAE 0W-20 meets the performance levels of:

- ❖ API SN
- ❖ ILSAC GF-5 Approved

Health and Safety

Please contact Pertamina Marketing Head Office for appropriate Material Safety Data Sheet containing information related to Work Health and Safety protection.

Phone: 62-21 3190 7190/5. Fax: 62-21 3148884/601

Website: www.pertaminalubricants.com Email: hsse.ptpl@pertamina.com

Disclaimer:

Information presented in this Product Data Sheet is as accurate as possible prior to printing. Such information is based upon standard industry tests under controlled laboratory conditions and presented as a guide only. To assess product suitability for its intended application, it is recommended that users refer to the latest version of the Product Data Sheet because the information contained herein is subject to change, without notice, due to the upgrades in product formulation, manufacturers' equipment specifications, user applications and storage.