

FASTRON SUPER SERIES



PASSENGER CAR MOTOR OILS

Product Description

A high quality gasoline engine oil

Applications

FASTRON SUPER SERIES is recommended for gasoline engine oil that requires above viscosity and performance level.

Typical Characteristics

Characteristics	Test Method	FASTRON SUPER	
SAE Viscosity Grade	-	15W - 40	20W - 50
Density at 15 °C, kg/L	ASTM D4052	0.8827	0.8881
Kinematic Viscosity, at 40 °C, cSt	ASTM D7279	108.9	176.7
at 100 °C, cSt	ASTM D7279	14.55	19.85
Viscosity Index	ASTM D2270	137	130
Flash Point, °C	ASTM D92	230	238
Pour Point, °C	ASTM D97	-24	-18
Total Base Number, mgKOH/g	ASTM D2896	7	7

Specification / Approvals

- API SL/CF

Superiorities

- Excellent oxidation stability that gives durable performance.
- Provides engine cleanliness and protection from excessive wear.

Health and Safety

Please contact our Industrial Marketing Head Office to get Material Safety Data Sheet as information for Health and Safety Protection
Phone: 62-21 3190 7190/5
Email: hsse.ptol@pertamina.com
www.pertaminalubricants.com

Disclaimer:

Information presented in this Product Data Sheet is as accurate as possible prior to printing. Such information is based upon standard industry tests under controlled laboratory conditions and presented as a guide only. To assess product suitability for its intended application, it is recommended that users refer to the latest version of the Product Data Sheet because the information contained herein is subject to change, without notice, due to the upgrades in product formulation, manufacturers' equipment specifications, user applications and storage.