

INDUSTRIAL & MARINE ENGINE OILS

Product Description

A synthetic high performance petrol and diesel engine oil.

FASTRON TECHNO PLUS SAE 0W-30 is highly recommended for the latest car generation from the leading car manufacturers that operate under extreme condition especially for gasoline and diesel engines with all types after treatment devices.

Typical Characteristics

Characteristics	Test Method	FASTRON TECHNO PLUS
SAE Viscosity Grade	-	0W - 30
Density at 15 °C, kg/L	ASTM D4052	0.8422
Kinematic Viscosity, at 40 °C, cSt	ASTM D7279	51.57
at 100 °C, cSt	ASTM D7279	10.05
Viscosity Index	ASTM D2270	186
Flash Point, °C	ASTM D92	252
Pour Point, °C	ASTM D5950	-39
Total Base Number, mgKOH/g	ASTM D2896	8

Specifications / Approvals

- ACEA C2

Superiorities

- Stable viscosity to ensure optimal acceleration and engine protection during startup and high-temperature operation.
- Exceptional resistance to oxidation and high temperature prolongs oil lifetime.
- Reduced oil volatility leads to minimal oil consumption and ensures optimal lubrication.
- Prevents corrosion, formation of piston deposits, and maintains engine cleanliness, thus extending engine lifetime.
- Very good soot control ability and acid neutralization, that are required by Exhaust Gas Recirculation (EGR) equipped engine.

Health and Safety

Please contact our Industrial Marketing Head Office to get Material Safety Data Sheet as information for Health and Safety Protection

Phone: 62-21 3190 7190/5

Email: hsse.ptpl@pertamina.com

www.pertaminalubricants.com

Disclaimer:

Information presented in this Product Data Sheet is as accurate as possible prior to printing. Such information is based upon standard industry tests under controlled laboratory conditions and presented as a guide only. To assess product suitability for its intended application, it is recommended that users refer to the latest version of the Product Data Sheet because the information contained herein is subject to change, without notice, due to the upgrades in product formulation, manufacturers' equipment specifications, user applications and storage.