

FASTRON XP SERIES



PASSENGER CAR MOTOR OILS

Product Description

A high performance petrol engine oil.

Applications

FASTRON XP SERIES is recommended for modern car generation from the leading car manufacturers, that operate under extreme condition.

Typical Characteristics

Characteristics	Test Method	FASTRON XP SERIES			
SAE Viscosity Grade	-	5W - 30	10W - 30	10W - 40	15W - 40
Density at 15 °C, kg/L	ASTM D4052	0.8560	0.8600	0.8637	0.8656
Kinematic Viscosity at 40 °C, cSt	ASTM D7279	64.53	69.02	97.00	102.1
at 100 °C, cSt	ASTM D7279	10.96	11.03	14.50	14.51
Viscosity Index	ASTM D2270	162	151	155	147
Flash Point, °C	ASTM D92	242	248	230	248
Pour Point, °C	ASTM D5950	-33	-30	-33	-27
Total Base Number, mg KOH/g	ASTM D2896	7	7	11	7

Specification / Approvals

- API SN/CF
- ACEA A3/B4 (for SAE 10W-40)

Superiorities

- Excellent oxidation stability that gives durable performance.
- Provides engine cleanliness and protection from excessive wear.

Health and Safety

Please contact our Industrial Marketing Head Office to get Material Safety Data Sheet as information for Health and Safety Protection
Phone: 62-21 3190 7190/5
Email: hsse.ptol@pertamina.com
www.pertamilubricants.com

Disclaimer:

Information presented in this Product Data Sheet is as accurate as possible prior to printing. Such information is based upon standard industry tests under controlled laboratory conditions and presented as a guide only. To assess product suitability for its intended application, it is recommended that users refer to the latest version of the Product Data Sheet because the information contained herein is subject to change, without notice, due to the upgrades in product formulation, manufacturers' equipment specifications, user applications and storage.