

# GREASE EPX-NL SERIES

## GREASE

### Product Description

high performance multipurpose lithium soap grease formulated from high quality base oil and latest technology additives.

### Applications

GREASE PERTAMINA EPX-NL series are recommended for various bearing type and gear in wide range of applications including industrial, automotive, construction and marine, with operating temperature up to 140°C.

### Typical Characteristics

Characteristics	Test Method	GREASE PERTAMINA EPX-NL SERIES	
NLGI Number	-	1	2
Thickener	-	Lithium 12-Hydroxystearate	Lithium 12-Hydroxystearate
Worked Penetration at 77 °F, 1/10 mm	ASTM D217	310 - 340	265 - 290
Dropping Point, °C	ASTM D2265	Min. 190	Min. 190
Colour	Visual	Yellow	Yellow
Base Oil Viscosity at 40 °C, cSt	ASTM D445	220	220

### Health and Safety

Please contact our Industrial Marketing Head Office to get Material Safety Data Sheet as information for Health and Safety Protection

Phone: 62-21 3190 7190/5

Email: [hsse.ptpl@pertamina.com](mailto:hsse.ptpl@pertamina.com)

[www.pertaminalubricants.com](http://www.pertaminalubricants.com)

### Disclaimer:

Information presented in this Product Data Sheet is as accurate as possible prior to printing. Such information is based upon standard industry tests under controlled laboratory conditions and presented as a guide only. To assess product suitability for its intended application, it is recommended that users refer to the latest version of the Product Data Sheet because the information contained herein is subject to change, without notice, due to the upgrades in product formulation, manufacturers' equipment specifications, user applications and storage.