

PASSENGER CAR MOTOR OILS

Product Description

A premium quality fully synthetic engine oil which is specially formulated in association with Lamborghini Squadra Corse. Designed for racing, it's using polyalphaolefin (PAO) base oil and high performance additives to give highest performance in its class.

Applications

FASTRON PLATINUM RACING SAE 10W-60 is designed for racing and also suitable for engine which requires SAE 10W-60 oil with above performance level.

Typical Characteristics

| Characteristics | Test Method | FASTRON PLATINUM RACING |
|-----------------------------------|-------------|-------------------------|
| SAE Viscosity Grade | - | 10W-60 |
| Density at 15 °C, kg/L | ASTM D4052 | 0.8627 |
| Kinematic Viscosity at 40 °C, cSt | ASTM D7279 | 157.4 |
| at 100 °C, cSt | ASTM D7279 | 23.05 |
| Viscosity Index | ASTM D2270 | 176 |
| Flash Point, °C | ASTM D92 | 254 |
| Pour Point, °C | ASTM D5950 | -42 |
| Total Base Number, mg KOH/g | ASTM D2896 | 11 |

Specification / Approvals

- API SN
- Lamborghini Squadra Corse

Superiorities

- Delivers maximal acceleration and power output.
- Excellent shear stability and high performance additives provide engine cleanliness and maximal protection from excessive wear, even in the most demanding racing application.
- Low evaporation level that gives low oil consumption and optimum lubrication.

Health and Safety

Please contact our Industrial Marketing Head Office to get Material Safety Data Sheet as information for Health and Safety Protection
Phone: 62-21 3190 7190/5
Email: hsse.ptol@pertamina.com
www.pertaminalubricants.com

Disclaimer:

Information presented in this Product Data Sheet is as accurate as possible prior to printing. Such information is based upon standard industry tests under controlled laboratory conditions and presented as a guide only. To assess product suitability for its intended application, it is recommended that users refer to the latest version of the Product Data Sheet because the information contained herein is subject to change, without notice, due to the upgrades in product formulation, manufacturers' equipment specifications, user applications and storage.